

# Technische Daten

## Barco/Folsom ImagePRO-II w/ dual Output/Audio



all-in one Video Scaler,  
Scan Converter und  
Switcher

dual Output Option

Audio Option

bis zu 2.560 x 1.600px

12bit processing

3D

### Eingänge

DVI-I: ..... digital: single link DVI bis 165MHz (DVI 1.0),  
..... dual link DVI bis 300MHz.  
..... analog: NTSC/PAL composite, Y/C, YPbPr (SD/HD),  
..... Computer: RGBHV, RGBS, RGsB  
..... aktiver Loop für alle Signale. EDID 1.3, HDCP 1.4.

HD-15 VGA: ..... NTSC/PAL composite, Y/C, YPbPr (SD/HD),  
..... Computer: RGBHV, RGBS, RGsB  
..... Sampling: 170MHz. aktiver Loop für alle Signale. EDID 1.3.

HDMI: ..... RGB and YCbCr; bis 2.048 x 1.080p @ 60 Hz  
..... (HDMI 1.4) und 1.920 x 1.200p @ 60 Hz  
..... EDID 1.3, HDCP 1.4, Deep color (30/36 bit).

DP: ..... bis 2.560 x 1.600 @ 60Hz (30 bit, DisplayPort 1.1a),  
..... HDCP 1.4.

SDI (2x): ..... SD-SDI (SMPTE 259MC, NTSC/PAL)  
..... HDSDI (SMPTE 292M, 296M)  
..... 3GSDI (SMPTE 424)  
..... Dual link HDSDI (SMPTE 372),  
..... Reclocked Loop output.

Audio: ..... 2x analog (XLR), 4x AES/EBU (BNC).  
..... 8x embedded HDMI / DP / SDI.

### Ausgänge

SDI/BarcoLink (2x): ..... SD-SDI (SMPTE 259MC, NTSC/PAL)  
..... HDSDI (SMPTE 292M, 296M)  
..... 3GSDI (SMPTE 424)  
..... Dual link HDSDI (SMPTE 372).

Video: ..... NTSC/PAL composite

DVI-D: ..... single link DVI bis 165MHz (DVI 1.0),  
..... dual link DVI bis 330MHz.  
..... EDID 1.3, HDCP 1.4.

HD-15 VGA: ..... NTSC/PAL composite, Y/C, YPbPr (SD/HD),  
..... RGBHV/RGBS/RGsB, EDID 1.3.

HDMI: ..... RGB/YCbCr @ 4:4:4, YCbCr @ 4:2:2 (HDMI 1.4),  
..... bis 2.048 x 1.080p @ 60Hz und 1.920 x 1.200 @ 60Hz.  
..... EDID 1.3, HDCP 1.4.

DP: ..... bis 2.560 x 1.600 @ 60Hz (30 bit, DisplayPort 1.1a),  
..... HDCP 1.4.

Audio: ..... 2x analog (XLR), 4x AES/EBU (BNC).  
..... 8x embedded HDMI / DP / SDI.

## Sync

Genlock ..... analog in/loop.  
 ..... bi-level/BB (SD), tri-level (HD).  
 3D ..... 3D sync in/out (miniDIN 3-pin)

## Remote

Remote: ..... USB 1.1  
 ..... Ethernet RJ-45 10/100Mbps

## Maße / Gewicht

+ 484 x 44 x 470 mm (BxHxT)  
 + Gewicht: 7,14 kg  
 + Maße Rackmodul: 520 x 75 x 580 mm (BxHxT)  
 + Gewicht inkl. Rackmodul: 10,8kg

## Netzanschluss

+ 100 - 240 V (AC), 47-63Hz  
 + 200 W  
 + Kaltgeräte-Buchse

## Produktansichten

